## **VT.57 BH**

Our VT flooring range comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.





FOR OFFICE USE ONLY		
	High Slip Bre-A/LEED Large Format	

# Bushhammered Properties



















### Other formats available



## Other finishes available

30cm

Ν	latural

#### Sizes available

120cm		60cm	A : : : : : : : : : : : : : : : : : : :	<
	60cm			60cm

#### Thickness available

10mm	A	

http://www.ecofriendlytiles.co.uk/eco/virtual-tray/essentials-collection



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk ecofriendlytiles.co.uk

# **Technical Specification** Code: VT.57 Bush Hammered



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & Chemical Properties	Norm/Test Method	Required Standard	Results
Water Absorption	ISO 10545-3	≤ 0.5%	0.04%
Length & Width	ISO 10545-2	± 0.6%	± 0.2%
Thickness	ISO 10545-2	± 5%	± 5%
Linearity	ISO 10545-2	± 0.5%	± 0.2%
Wedging	ISO 10545-2	± 0.6%	± 0.2%
Warpage	ISO 10545-2	± 0.5%	± 0.2%
Flexion Resistance	ISO 10545-4	≥ 35 N/mm²	51.1N/m <sup>2</sup>
Deep Abrasion Resistance	ISO 10545-6	Max 175 mm³	126 mm³
Frost Resistance	ISO 10545-12	No evidence of surface change	Frost Resistant
Coefficient of Linear Thermal Expansion	ISO 10545-8	≤ 9x10 <sup>-6</sup> °C <sup>-1</sup>	≤ 6.2x10 <sup>-6</sup> °C <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	No visible defects shown	Resistant
Colour Stability	DIN 51094	No noticeable colour variation	Resistant
Chemical Resistance	ISO 10545-13	No noticeable signs of chemical attack	Resistant
Coeffcient of Friction	ASTM C 1028	≥ 0.60	Meets or exceeds requirements
	DIN 51130	-	R11

#### Certifications

























