VT.58 BH

Our VT flooring range comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.







Bushhammered **Properties**























Other formats available



Mosaic

Other finishes available



Sizes available

20cm	1	
	٧	60cm

60cm



Thickness available

http://www.ecofriendlytiles.co.uk/eco/virtual-tray/essentials-collection



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk ecofriendlytiles.co.uk

Technical Specification Code: VT.58 Bush Hammered



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

			<u> </u>
Physical & Chemical Properties	Norm/Test Method	Required Standard	Results
Water Absorption	ISO 10545-3	≤ 0.5%	0.04%
Length & Width	ISO 10545-2	± 0.6%	± 0.2%
Thickness	ISO 10545-2	± 5%	± 5%
Linearity	ISO 10545-2	± 0.5%	± 0.2%
Wedging	ISO 10545-2	± 0.6%	± 0.2%
Warpage	ISO 10545-2	± 0.5%	± 0.2%
Flexion Resistance	ISO 10545-4	≥ 35 N/mm²	51.1N/m ²
Deep Abrasion Resistance	ISO 10545-6	Max 175 mm³	126 mm³
Frost Resistance	ISO 10545-12	No evidence of surface change	Frost Resistant
Coefficient of Linear Thermal Expansion	ISO 10545-8	≤ 9x10 ⁻⁶ °C ⁻¹	≤ 6.2x10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	ISO 10545-9	No visible defects shown	Resistant
Colour Stability	DIN 51094	No noticeable colour variation	Resistant
Chemical Resistance	ISO 10545-13	No noticeable signs of chemical attack	Resistant
Coeffcient of Friction	ASTM C 1028	≥ 0.60	Meets or exceeds requirements
	DIN 51130	-	R11

Certifications

























