Technical Specification Code: VT.218 Grip



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

| | | | | WWW.ccomenarythes.co.ak |
|---|------------------|----------------------------------|--|-------------------------|
| Physical & Chemical Properties | Norm/Test Method | Required Standard | Results | |
| Thickness | EN ISO 10545-2 | ± 5.0% / ± 0.5mm | Conforms | |
| Straightness of sides | EN ISO 10545-2 | ± 0.5% / ± 1.5mm | Conforms | |
| Rectangularity | EN ISO 10545-2 | ± 0.6% / ± 2.0mm | Conforms | |
| Surface Flatness | EN ISO 10545-2 | ± 0.5% / ± 2.0mm | Conforms | |
| Water Absorption | EN ISO 10545-3 | ≤ 0.5% | 0.03% | |
| Flexion Resistance | EN ISO 10545-4 | S ≥ 700 N (< 7.5mm) | S 3.038 N | |
| | | $R \ge 35 \text{ N/mm}^2$ | R ≥ 50.5 N/mm ² | |
| Impact Resistance | EN ISO 10545-5 | Declared Value | 0.88 | |
| Abrasion Resistance | EN ISO 10545-6 | ≤ 175mm2 | 124mm³ | |
| Coefficient of Linear Thermal Expansion | EN ISO 10545-8 | - | $\partial = 7.3 \times 10^{-6} ^{\circ}\text{C}^{-1}$ | |
| Resistance to Thermal Shocks | EN ISO 10545-9 | Pass according to EN ISO 10545-1 | No Damage | |
| Frost Resistance | EN ISO 10545-12 | Pass according to EN ISO 10545-1 | No Damage | |
| Resistance to Chemicals | EN ISO 10545-13 | UB Min. | UA ULA UHA | |
| Resistance to Stains | EN ISO 10545-14 | Declared Value | Class 5 | |
| Lead and Cadmium Discharge | EN ISO 10545-15 | Declared Value | Within Limit | |
| Slip Resistance | DM. 236/89 BCRA | > 0.40 | > 0.40 | |
| | ASTM Wet and Dry | > 0.60 | > 0.60 | |
| | DIN 51130 | - | R11 | |
| | DIN 51097 | - | A+B+C | |
| Pendulum Test | UNI EN 130036 | ≥36 | ≥36 | |
| | | | | |

Certifications













