VT.446P

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.



Polished **Properties** Colours Recycled

Other formats available







Mosaic






Other finishes available

Natural

Semi Polished

Sizes available





| 60cm | | 10mm ‡ |
|------------|----------------|--------|
| | ∢ 120cm | |

www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.446P



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

| Physical & chemical properties | Norm/test method | Required Standard | Results |
|--------------------------------|------------------------|----------------------------|------------------|
| Thickness | EN ISO 10545-2 | ± 5.0% / ± 0.5mm | Conforms |
| Straightness of sides | IEN ISO 10545-2 | ± 0.5% / ± 1.5mm | Conforms |
| Rectangularity | EN ISO 10545-2 | ± 0.6% / ± 2.0mm | Conforms |
| Warpage | EN ISO 10545-2 | ± 0.5% / ± 2.0mm | Conforms |
| Water absorption | EN ISO 10545-3 | ≤ 0.5% | ≤ 0.05% |
| Flexion Resistance | EN ISO 10545-4 | $AR \ge 35 \text{ N/mm}^2$ | ≥ 35 N/mm² |
| Abrasion Resistance | IEN ISO 10545-7 | - | 4 |
| Frost Resistance | EN ISO 10545-12 | - | Stan ds the test |
| Resistance to Chemicals | EN ISO 10545-13 | UB Min. | Class A |
| Resistance to Stains | EN ISO 10545-14 | Declared Value | Minimum Class 3 |
| Slip Resistance | DIN 51130 | - | - |
| | BS-7976-2:2002 Pedulum | - | - |

Certifications











