
## **VT.68BH**


Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.











## www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: VT.68BH



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results	
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	± 0.5mm	
Straightness of sides	IEN ISO 10545-2	± 0.5% / ± 1.5mm	± 0.8mm	
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	± 1.5mm	
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	± 1.8mm	
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%	
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm²	≥ 50 N/mm²	
Deep Abraision Resistance	EN ISO 10545-6	≤ 175 mm³	< 150 mm <sup>3</sup>	
Linear Thermal Expansion	EN ISO 10545-8		≤ 6.2*10 <sup>-6</sup> °C	
Resistance to Thermal Shock	EN ISO 10545-9	-	Resistant	
Frost Resistance	EN ISO 10545-12	UB Min.	Resistant	
Resistance to Chemicals	EN ISO 10545-13	UB Min	Resistant	
Resistance to Stains	EN ISO 10545-14	≥ Class 3	Class 5	
Slip Resistance	DIN 51130	-	R10	
	BS 7976-2:2002 Pendulum	-		

## Certifications











