## **VT.382SP**

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.



## Semi-polished Properties LEED EPD R9 More Thermal Chemical Frost Colours Carbon Shock PTV 36+ Resistant Resistant Offset Resistant Available Other formats available Other finishes available 20mm 30mm Mosaic Grip Natural Paver Paver Sizes available 160 cm 160cm ≺-----> 320 cm **∢-----**160cm 120cm 9mm 120cm 278cm **∢-----**120cm 120cm 9mm Î 9mm 60cm -----240cm <----</td> 60cm 60cm 9mm www.ecofriendlytiles.co.uk <----> 120cm ECO 30cm 9mm FRIENDLY London **∢ - - - - - - →** 60cm **TILES®** SW6 3BN 9mm The planet, covered **★ - - - - - - - - →** 60cm

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road

## 0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: VT.382SP



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN 0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Straightness of sides	IEN ISO 10545-2	± 0.3% / ± 1.0mm	Conforms
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm <sup>2</sup>	≥ 48 N/mm <sup>2</sup>
Abrasion Resistance	IEN ISO 10545-6	≤ 175mm²	< 150mm <sup>2</sup>
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	< 6.6*10 <sup>-6</sup> °C
Resistance to Thermal Shocks	EN ISO 10545-9	-	Stands the test
Frost Resistance	EN ISO 10545-12	-	Stands the test
Resistance to Chemicals	EN ISO 10545-13	UB Min.	Class A
Resistance to Stains	EN ISO 10545-14	Declared Value	5
Slip Resistance	DIN 51130	-	R9
	BS-7976-2:2002 Pedulum	-	PTV 36+

Certifications



This technical information sheet is not a guarantee of performance and is not a warranty, either explicit or implicit. Rather, it tries to summarize for the designer, installer or developer the technical data provided to Eco Friendly Tiles by the independent tile manufacturer. This information may not be applicable in all geographical areas. It is the responsibility of those individuals who are referring to this document to independently research and determine which tiles are suitable for a given project according to applicable British or International Standards and any governing legislative requirements. This document cannot be used as expert opinion, evidence or in any legal or administrative procedure unless authorized by Eco Friendly Tiles Ltd.