VT.351

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.



Natural

Properties























Recycled Content

40%

Other formats available





Other finishes

Polished

Sizes available







www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.351



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	± 5.0%
Straightness of sides	IEN ISO 10545-2	± 0.5% / ± 1.5mm	± 0.1%
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	± 0.1%
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	± 0.2%
Water absorption	EN ISO 10545-3	≤ 0.5%	0.03% - 0.06%
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm²	49 N/mm²
Resistsance to Abrasion	EN ISO 10545-6	≤ 175 mm³	≤ 140 mm³
Coefficient of Lineaer Thermal Expansion	EN ISO 10545-8	-	6.5x10 ⁻⁶ °C ⁻¹
Resistance to Thermal Shocks	EN ISO 10545-9	Resistant	Resistant
Frost Resistance	EN ISO 10545-12	Resistant	Conforms
Resistance to Chemicals	EN ISO 10545-13	B minimum	LA, HA
Resistance to Staining	EN ISO 10545-14	-	Minimum Class 2
Slip Resistance	DIN 51130	-	R9
	BS 7976-2:2002 Pendulum	-	

Certifications













