## VT.496G

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.





MOBILE SAMPLE LIBRARY RI	EFERENCE	
Hi	ood Look gh Slip orcelain	

Grip									
ropert	es								
Carbon Offset	Chemical Resistant	Frost Resistant	Thermal Shock Resistant	More Colours Available	EPD (LEED	BREEAM	R11	Content	e Consumer Recycled Content
ther fo	ormats ava	ailable					Other fini	ishes availa	ble



## www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: VT.496G



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Straightness of sides	IEN ISO 10545-2	± 0.5% / ± 1.5mm	Conforms
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.05%
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm <sup>2</sup>	≥ 35 N/mm²
Abrasion Resistance	IEN ISO 10545-7	-	Class 4
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	< 7.1*10 <sup>-6</sup> °C <sup>-1</sup>
Resistance to Thermal Shocks	EN ISO 10545-9	-	Conforms
Resistance to Crazing	EN ISO 10545-11	-	≤ 0.2mm/m
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	Min. Class B	GA
Resistance to Stains	EN ISO 10545-14	Declared Value	Minimum Class 4
Slip Resistance	DIN 51130	-	R11
	BS 7976-2:2002 Pendulum	-	-

## Certifications











