


VT.152G


Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.













www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.152G



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

planet comiere	info@ecorriendlytiles.co.uk
e planet, covered	www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results	
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%	
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm²	Conforms	
Frost Resistance	EN ISO 10545-12	-	Frost Proof	
Resistance to Chemicals	EN ISO 10545-13	B Min.	Unaffected	
Slip Resistance	DIN 51130	-	R11	
	BS 7976-2:2002 Pendulum	-	-	

Certifications













