VT.168PAV

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.





OBILE SAN	IPLE LIBRA	ARY REFERENCE	
*		Wood Look High Slip Paver Porcelain	

Properties	
Carbon Chemical Offset Resistant Res	ISO (POUT) (R11) (20%) (PTV 36+ Recycled Content)
Other formats available	Other finishes available
Solid	Natural
Sizes available	Natural



www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.168PAV



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Complies
Straightness of sides	EN ISO 10545-2	± 0.3% / ± 0.8mm	Complies
Rectangularity	EN ISO 10545-2	± 0.3% / ± 1.5mm	Complies
Surface Flatness	EN ISO 10545-2	± 0.4% / ± 1.8mm	Complies
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%
Flexion Resistance	EN ISO 10545-4	$R \ge 35 \text{ N/mm}^2$	≥ 45 N/mm²
Crazing Resistance	EN ISO 10545-11	-	Resistant
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	GB Min.	Compliant
Resistance to Stains	EN ISO 10545-14	Min Class 3.	Compliant
Slip Resistance	DIN 51130	-	R11
	BS-7976-2:2002 Pendulum	-	PTV 36+

Certifications











