## **VT.254**

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.


30cm


60cm













www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: VT.254



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

covered	info@ecomenarythes.co.uk
, covereu	www.ecofriendlytiles.co.ul

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% max	± 5%
Length and Width	IEN ISO 10545-2	± 0.6% max	± 0.1%
inearity	EN ISO 10545-2	± 0.5%	± 0.1%
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	± 0.2%
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm²	49 N/mm²
Abrasion Resistance	EN ISO 10545-6	max 175mm³	140mm³
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	6.5X10 <sup>-6</sup> °C <sup>-1</sup>
Resistance to Thermal Shocks	EN ISO 10545-9	-	Resistant
rost Resistance	EN ISO 10545-12	UB Min.	Conforms
Resistance to Chemicals	EN ISO 10545-13	UB Min	Conforms
Stain Resistance	EN ISO 10545-14	-	Conforms
Slip Resistance	DIN 51130	-	R10
	BS 7976-2:2002 Pendulum	-	-

## Certifications











