
VT.408PAV


Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.















Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.408PAV



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results	
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Compliant	
Straightness of sides	EN ISO 10545-2	± 0.5% / ± 1.5mm	Compliant	
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Compliant	
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	Compliant	
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%	
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm²	≥ 45 N/mm²	
Cracking Resistance	EN ISO 10545-11	-	Resistant	
Frost Resistance	EN ISO 10545-12	-	Resistant	
Resistance to Chemicals	EN ISO 10545-13	UB Min.	Compliant	
Resistance to Stains	EN ISO 10545-14	Declared Value	Compliant	
Slip Resistance	DIN 51130	-	R11	
	BS 7976-2:2002 Pendulum	-	-	

Certifications













