
VT.496G

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.





CARLES CONTRA CO.	\$10 PM-1	130000000000000000000000000000000000000	
MOBILE SAMPLE LIBRAR	/ REFERENCE		
	Wood Look High Slip Porcelain		

Grip	
Properties	
Carbon Chemical Frost Shock Resistant Resistan	R11) Recycled Content Pre Consumer Recycled Content Other finishes available
20mm	
Paver	Natural



www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.496G



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Length & Width	IEN ISO 10545-2	± 0.5% / ± 1.5mm	Conforms
Wedging	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms
Warpage of Edges	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	Conforms
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm²	9mm ≥ 45 N/mm²
Abrasion Resistance	EN ISO 10545-7	-	Conforms
Resistance to Thermal Shocks	EN ISO 10545-9	-	Resists
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	Min GB	Conforms
Resistance to Stains	EN ISO 10545-14	Min Class 3	Conforms
Slip Resistance	DIN 51130	-	R11
	BS 7976-2:2002 Pendulum	-	-

Certifications











