
VT.586SP


Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.











MOBILE SAMPLE LIBRARY REFERENCE Concrete Look Semi-Polished



FRIENDLY TILES® The planet, covered

www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.586SP



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

et, covered	into eccontentialy the s.co. ak
ei, covereu	www.ecofriendlytiles.co.ul
	www.ecomenarythes.co.ur

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	± 5.0%
Length and Width	EN ISO 10545-2	±0.6% Max	± 0.2%
Linearity	EN ISO 10545-2	± 0.5% Max	± 0.2%
Warpage	EN ISO 10545-2	± 0.5% Max	± 0.2%
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.06%
Breaking Modulus	EN ISO 10545-4	≥ 1300N	50 N/mm² (561kg/cm²)
Breaking Strength	EN ISO 10545-4	≥ 700N	2500 N ≥ 700N
Deep Abrasion Resistance	EN ISO 10545-6	≤ 175 mm³	< 143 mm ³
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	< 9*10 ⁻⁶ °C ⁻¹	< 6.5*10 ⁻⁶ °C ⁻¹
Frost Resistance	EN ISO 10545-12	-	Frost Proof
Resistance to Chemicals	EN ISO 10545-13	UB Minimum	Compliant
Resistance to Stains	EN ISO 10545-14	1 < X < 5	Class 5
Colour Resistance to Light	DIN 51094	-	No change
Slip Resistance	DIN 51130	-	-
	BS 7976-2:2002 Pendulum	-	-

Certifications













