6.2.A(2)SP

Lots of finishes in lots of colours, and each tile with an eco-advantage. From lighter shades to deep, rich colours, there's versatility aplenty whatever the setting in our Volta Range thanks to multiple sizes and slip ratings. Some tiles include 40% pre-or-post consumer recycled content...but all carry impressive environmental certification.





MOBILE SAMPLE LIBRARY REFERENCE

Stone Look High Slip

Porcelain





Properties

















Other formats available

Other finishes available







Natural

Grip

Sizes available







www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: 6.2.A(2)SP



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	ISO 10545-2	± 5.0% / ±0.5mm	Conforms
Straightness of sides	ISO 10545-2	± 0.5% / ± 1.5mm	Conforms
Rectangularity	ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Flatness	ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	ISO 10545-3	≤ 0.5%	Conforms
Average Bending Strength	ISO 10545-4	35 N/mm² min.	Conforms
Frost Resistance	ISO 10545-12	-	Required
Resistance to Chemicals	ISO 10545-13	GB min.	
Slip Resistance	DIN 51130		-
	BS 7976-2:2002 Pendulum		

Certifications











