

6.11.DBH

Lots of finishes in lots of colours, and each tile with an eco-advantage. From lighter shades to deep, rich colours, there's versatility aplenty whatever the setting in our Volta Range thanks to multiple sizes and slip ratings. Some tiles include 40% pre-or-post consumer recycled content...but all carry impressive environmental certification.



Bush H	ammere	d							
Properties									
Carbon Offset	Chemical Resistant	Frost Resistant	Thermal Shock Resistant	More Colours Available	LEED	BREEAM	ISO 9001	R11 PTV	24 36+ Rec Co
Other formats available					_		Other finishes	availab	
Mosaic								Natural	



www.ecofriendlytiles.co.uk



Technical Specification Code: 6.11.DBH



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Length and Width	EN ISO 10545-2	± 0.6% max	±0.2% max
Thickness	EN ISO10545-2	±5.0% max	±5.0% max
Water Absorption	EN ISO 10545-3	≤0.5%	<0.05%
Bending Strength	EN ISO 10545-4	≥35N/mm²	>42N/mm²
Resistance to Deep Abrasion	EN ISO 10545-6	≤175N/mm²	140mm²
Thermal Expansion Coefficient	EN ISO 10545-8	-	7MK ⁻¹
Thermal Shock Resistance	EN ISO 10545-9	-	Resistant
Frost Resistance	EN ISO 10545-12	-	Frost Resistance
Chemical Resistance	EN ISO 10545-13	UB min.	Unaffected
Slip Resistance	DIN51130	-	R11
	BS 7976-2:2002 Pendulum	-	PTV 36+

Certifications











