## VT.341

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.



#### Natural

### **Properties**

















#### Other formats available













Polished

Sizes available









## FRIENDLY TILES® The planet, covered

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

www.ecofriendlytiles.co.uk

0844 980 2233 info@ecofriendlytiles.co.uk

# Technical Specification Code: VT.341



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results	
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms	
Straightness of sides	EN ISO 10545-2	± 0.5% / ± 1.5mm	Conforms	
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms	
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms	
Water absorption	EN ISO 10545-3	≤ 0.5%	Conforms	
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm²	Conforms	
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	7x10 <sup>-6</sup> °C <sup>-1</sup>	
Resistance to Thermal Shocks	EN ISO 10545-9	-	Resistant	
Frost Resistance	EN ISO 10545-12	UB Min.	Resistant	
Resistance to Chemicals	EN ISO 10545-13	Declared Value	Resistant	
Resistance to Staining	EN ISO 10545-14	Minimum Class 3	Conforms	
Slip Resistance	DIN 51130	-	R10	
	BS 7976-2:2002 Pendulum	-	-	

#### Certifications











