## **VT.359**

Our Cascade Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.






MOBILE SAMPLE LIBRARY REFERENCE

Terrazzo Look Porcelain











Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: VT.359



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Dimensions	EN ISO 10545-2	-	Complies
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%
Flexion Resistance	EN ISO 10545-4	AR ≥ 35 N/mm²	≥ 35 N/mm²
Breaking Strength	EN ISO 10545-4	≥ 1300 N for thickness ≥ 7.5mm	Complies
Impact Resistance	EN ISO 10545-5	-	> 0.75
Abraision Resistance	EN ISO 10545-7	-	Class 0-5
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	< 7.1*10 <sup>-6</sup> °C
Resistance to Thermal Shocks	EN ISO 10545-9	-	Complies
Moisture Expansion	EN ISO 10545-10	-	≤ 0.2mm
Crazing Resistance	EN ISO 10545-11	-	Complies
Frost Resistance	EN ISO 10545-12	UB Min.	Complies
Resistance to Chemicals	EN ISO 10545-13	Declared Value	Class A
Resistance to Staining	EN ISO 10545-14	Minimum Class 3	≥ 4
Slip Resistance	DIN 51130	-	R9

## Certifications















BS 7976-2:2002 Pendulum