## 5.2.B(2)G

A brilliant multi-tasker, bristling with eco certifications and slip rating options. If you like your stone and concrete effect tiles honed, polished, flamed or flate, we're ready with the whitest whites, the subtlest greys and the richest blacks to help make a statement of creative intent.

30cm

60cm









## Technical Specification Code: 5.2.B(2)G



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

anet, covered www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Straightness of sides	IEN ISO 10545-2	± 0.5% / ± 1.5mm	Conforms
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms
Surface Flatness	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.05%
Flexion Resistance	EN ISO 10545-4	R ≥ 35 N/mm²	R ≥ 50 N/mm <sup>2</sup>
Abrasion Resistance	EN ISO 10545-6	≤ 175mm³	135mm³
Coefficient of Linear thermal Expansion	EN ISO 10545-8	-	a=7x10-6°C-1
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	UB Min	Resistant
Slip Resistance	DIN 51130	-	R12
	BS 7976-2:2002 Pendulum	-	

## Certifications













