
## 5.2.B(2)


Our EPD Group 1 - Garda Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.








## Natural **Properties** EPD GROUF LEED 9001 More Recycled Carbon Colours Shock Resistant Resistant Resistant GARDA Other formats available Other finishes available 20mm Grip Decor Mosaic Paver Sizes available







Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

## Technical Specification Code: 5.2.B(2)



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Straightness of sides	IEN ISO 10545-2	± 0.5% / ± 1.5mm	Conforms
Rectangularity	EN ISO 10545-2	± 0.6% / ± 2.0mm	Conforms
Surface Flatness	EN ISO 10545-2	± 0.5% / ± 2.0mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.05%
Flexion Resistance	EN ISO 10545-4	R ≥ 35 N/mm²	R ≥ 50 N/mm <sup>2</sup>
Abrasion Resistance	EN ISO 10545-6	≤ 175mm³	135mm³
Coefficient of Linear thermal Expansion	EN ISO 10545-8	-	a=7x10-6°C-1
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	UB Min	Resistant
Slip Resistance	DIN 51130	-	R10
	BS 7976-2:2002 Pendulum	-	

## Certifications











