
# 5.2.E(3)

Our EPD Group 1 - Garda Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.










## Other formats available

Decor

### Sizes available



# www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

# Technical Specification Code: 5.2.E(3)



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	Conforms
Straightness of sides	IEN ISO 10545-2	± 0.3% / ± 0.8mm	Conforms
Rectangularity	EN ISO 10545-2	± 0.3% / ± 1.5mm	Conforms
Surface Flatness	EN ISO 10545-2	± 0.4% / ± 1.8mm	Conforms
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%
Flexion Resistance	EN ISO 10545-4	R ≥ 35 N/mm²	R ≥ 48 N/mm²
Abrasion Resistance	EN ISO 10545-6	≤ 175mm³	<150mm³
Coefficient of Linear thermal Expansion	EN ISO 10545-8	-	a=6.1x10-6°C-1
Frost Resistance	EN ISO 10545-12	-	Resistant
Resistance to Chemicals	EN ISO 10545-13	UB Min	Resistant
Slip Resistance	DIN 51130	-	R9
	BS 7976-2:2002 Pendulum	-	PTV 36+

#### Certifications











