VT.645SP

Our EPD Group 1 - Garda Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.









GARDA

Shock


Resistant


Resistant

Other formats available

Other finishes available

Sizes available





www.ecofriendlytiles.co.uk



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

Technical Specification Code: VT.645SP



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% Max	Complies
Straightness of Sides	EN ISO 10545-2	±0.6% Max	Complies
Rectangularity	EN ISO 10545-2	± 0.5% Max	Complies
Surface Flatness	EN ISO 10545-2	± 0.5% Max	Complies
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.1%
Modulus of Rupture	EN ISO 10545-4	≥ 35 N/mm²	≥ 48 N/mm²
Impact Resistance	EN ISO 10545-5	-	140 mm³
Resistance to Deep Abrasion	EN ISO 10545-6	≤ 175 mm³	> 0.80
Thermal Expansion Coefficient	EN ISO 10545-8	-	< 6.6*10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	EN ISO 10545-9	-	No damage
Frost Resistance	EN ISO 10545-12	-	No damage
Resistance to Chemicals	EN ISO 10545-13	B Minimum	A, LA, HA
Resistance to Stains	EN ISO 10545-14	-	5
Slip Resistance	DIN 51130	-	R9
Pendulum Test Value		-	PTV 36+

Certifications













