



VT.255

Our EPD Group 2 - Como Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.




MOBILE SAMPLE LIBRARY REFERENCE




Concrete Look
High Slip
EPD Group 2 - Como Range

Natural


Properties



Carbon Offset




Chemical Resistant




Frost Resistant




Thermal Shock Resistant



More Colours Available




EPD GROUP 2
COMO



BREEAM




LEED




EMAS




ISO 14001



ISO 9001



R10



UP TO 40%
Recycled Content

Other formats



20mm
Paver


Other finishes



Grip


Sizes available

75cm




150cm

6mm




75cm




75cm

6mm




60cm




120cm

8mm




60cm




60cm

8mm




30cm



60cm

8mm





ECO FRIENDLY
TILES®
The planet, covered

www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd
Ground Floor, Solon House
40a Peterborough Road
London
SW6 3BN
0844 980 2233
info@ecofriendlytiles.co.uk

Technical Specification

Code: VT.255



Eco Friendly Tiles Ltd
Ground Floor, Solon House
40a Peterborough Road
London
SW6 3BN
0844 980 2233
info@ecofriendlytiles.co.uk
www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Thickness	EN ISO 10545-2	± 5.0% max	± 5%
Length and Width	EN ISO 10545-2	± 0.6% max	± 0.1%
Linearity	EN ISO 10545-2	± 0.5%	± 0.1%
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	± 0.2%
Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm ²	49 N/mm ²
Abrasion Resistance	EN ISO 10545-6	max 175mm ³	140mm ³
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	6.5X10 ⁻⁶ °C ⁻¹
Resistance to Thermal Shocks	EN ISO 10545-9	-	Resistant
Frost Resistance	EN ISO 10545-12	UB Min.	Conforms
Resistance to Chemicals	EN ISO 10545-13	UB Min	Conforms
Stain Resistance	EN ISO 10545-14	-	Conforms
Slip Resistance	DIN 51130	-	R10
	BS 7976-2:2002 Pendulum	-	-

Certifications



This technical information sheet is not a guarantee of performance and is not a warranty, either explicit or implicit. Rather, it tries to summarize for the designer, installer or developer the technical data provided to Eco Friendly Tiles by the independent tile manufacturer. This information may not be applicable in all geographical areas. It is the responsibility of those individuals who are referring to this document to independently research and determine which tiles are suitable for a given project according to applicable British or International Standards and any governing legislative requirements. This document cannot be used as expert opinion, evidence or in any legal or administrative procedure unless authorized by Eco Friendly Tiles Ltd.