

### **VT.283P**


Our EPD Group 2 - Como Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.











150cm

## TILES® The planet, covered

#### www.ecofriendlytiles.co.uk

Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

# Technical Specification Code: VT.283P



Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk

www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results	
Thickness	EN ISO 10545-2	± 5.0% / ± 0.5mm	± 5%	
Length and Width	EN ISO 10545-2	± 0.5% / ± 1.5mm	± 0.1%	
Linearity	EN ISO 10545-2	± 0.6% / ± 2.0mm	± 0.1%	
Warpage	EN ISO 10545-2	± 0.5% / ± 2.0mm	± 0.2%	
Water absorption	EN ISO 10545-3	≤ 0.5%	0.05% - 0.07%	
Flexion Resistance	EN ISO 10545-4	≥ 35 N/mm²	≥ 55 N/mm²	
Resistance to Deep Abrasion	EN ISO 10545-6	≤ 175 mm³	130 mm³	
Coefficient of Linear Thermal Expansion	EN ISO 10545-8	-	< 6.2*10 <sup>-6</sup> °C <sup>-1</sup>	
Resistance to Thermal Shocks	EN ISO 10545-9	-	Resistant	
Frost Resistance	EN ISO 10545-12	-	Resistant	
Resistance to Chemicals	EN ISO 10545-13	-	Conforms	
Stains Resistance	EN ISO 10545-14	Class 3 Min.	Class 5	
Slip Resistance	DIN 51130	-	-	
	BS 7976-2:2002 Pendulum	-	-	

#### Certifications













