


6.15.BPAV

Our EPD Group 3 - Rhine Range for Floor & Wall comes in hundreds of different designs, colours, slip ratings and finishes. Much of the range offers our revolutionary GresGrip™ finish and is accredited to rigorous eco-friendly standards (including LEED/BREEAM etc) to help specifiers meet the sustainability goals of their clients.




MOBILE SAMPLE LIBRARY REFERENCE




Granular Concrete Look Paver
High Slip, GresGrip™
EPD Group 3 - Rhine Range

GresGrip™ Natural


Properties




Carbon Offset




Chemical Resistant




Frost Resistant




Thermal Shock Resistant




More Colours Available




EPD GROUP 3
RHINE




LEED




BREEAM




EMAS




ISO 9001




ISO 14001



R11




PTV 40+




OVER 40%
Recycled Content


Other formats available



Solid




Mosaic



Decor

Other finishes available

Sizes available



www.ecofriendlytiles.co.uk



ECO FRIENDLY
TILES®
The planet, covered

Eco Friendly Tiles Ltd
Ground Floor, Solon House
40a Peterborough Road
London
SW6 3BN
0844 980 2233
info@ecofriendlytiles.co.uk

Technical Specification

Code: 6.15.BPAV



Eco Friendly Tiles Ltd
Ground Floor, Solon House
40a Peterborough Road
London
SW6 3BN
0844 980 2233
info@ecofriendlytiles.co.uk
www.ecofriendlytiles.co.uk

Physical & chemical properties	Norm/test method	Required Standard	Results
Length and Width	EN ISO 10545-2	± 0.6% max	±0.2% max
Thickness	EN ISO 10545-2	±5.0% max	±5.0% max
Linearity	EN ISO 10545-2	±0.5% max	±0.2% max
Wedging	EN ISO 10545-2	±0.6% max	±0.2% max
Warpage	EN ISO 10545-2	±0.5% max	±0.2% max
Water Absorption	EN ISO 10545-3	≤0.5%	<0.05%
Bending Strength	EN ISO 10545-4	≥35 N/mm ²	> 48 N/mm ²
Resistance to Deep Abrasion	EN ISO 10545-6	≤175 N/mm ²	140mm ²
Thermal Expansion Coefficient	EN ISO 10545-8	-	7MK ⁻¹
Thermal Shock Resistance	EN ISO 10545-9	-	Resistant
Frost Resistance	EN ISO 10545-12	-	Frost Resistance
Chemical Resistance	EN ISO 10545-13	UB min.	Unaffected
Stain Resistance	EN ISO 10545-14	-	class 5
Colour Resistance to Light	DIN 51094	-	No change in brightness or colour
Slip Resistance	DIN51130	-	R11
	BS 7976-2:2002 Pendulum	-	PTV 40+

Certifications



This technical information sheet is not a guarantee of performance and is not a warranty, either explicit or implicit. Rather, it tries to summarize for the designer, installer or developer the technical data provided to Eco Friendly Tiles by the independent tile manufacturer. This information may not be applicable in all geographical areas. It is the responsibility of those individuals who are referring to this document to independently research and determine which tiles are suitable for a given project according to applicable British or International Standards and any governing legislative requirements. This document cannot be used as expert opinion, evidence or in any legal or administrative procedure unless authorized by Eco Friendly Tiles Ltd.