
VS.60P

Our EPD Group 4 - Shannon Range are a selection of Ultra-thin - from just 3.5mm - yet so strong it can be laid in 3m x 1m slabs on floors, walls or as an overlay. With low embodied carbon, up to 40% pre-consumer recycled content, flexible sizes and over one hundred colours and finishes, it's time to join the surface revolution. With a LEED and product specific EPD certifications, it's a range perfectly in step with 21st century living.













Shock
















Other formats available

Other finishes available

Sizes available









Eco Friendly Tiles Ltd Ground Floor, Solon House 40a Peterborough Road London

www.ecofriendlytiles.co.uk

0844 980 2233 info@ecofriendlytiles.co.uk

SW6 3BN

Technical Specification Code: VS.60P



Eco Friendly Tiles Limited Ground Floor, Solon House 40a Peterborough Road London SW6 3BN

0844 980 2233 info@ecofriendlytiles.co.uk www.ecofriendlytiles.co.uk

Certifications





















Physical & chemical properties	Norm/test method	Shannon 12+ Polished	
Length & Width (1620x3240 mm)	ISO 10545-2	Minimum size: ≥ 1630x3250 mm	
Weight	Factory	Average value 30kg/m²	
Surface quality/% of tiles with no visible flaws	ISO 10545-2	> 95%	
Water absorption	ISO 10545-3	Average Value ≤ 0.1%	
Breaking strength in N (samples 400x800mm)	ISO 10545-4	> 4000	
Modulus of rupture in N/mm² (samples 400x800mm)	ISO 10454-4	Average value 50	
Resistance to deep abrasion	ISO 10545-6	≤ 175mm³	
Coefficient of linear thermal expansion / 10 ⁻⁶ / 0 ^c	ISO 10545-8	Average value 6.6	
Resistance to thermal shock	ISO 10545-9	Compliant	
Resistance to freeze-thaw	ISO 10545-12	Compliant	
Chemical resistance	ISO 10545-13	Class: from A to C	
Stain resistance	ISO 10545-14	Class: from 2 to 5	
Coefficient of friction	BS 7976-2:2002 Pendulum	-	
	EN 13501 (rev. 2005)	-	
Fire reaction		A2 - s1,d0	

This technical information sheet is not a guarantee of performance and is not a warranty, either explicit or implicit. Rather, it tries to summarize for the designer, installer or developer the technical data provided to Eco Friendly Tiles by the independent tile manufacturer. This information may not be applicable in all geographical areas. It is the responsibility of those individuals who are referring to this document to independently research and determine which tiles are suitable for a given project according to applicable British or International Standards and any governing legislative requirements. This document cannot be used as expert opinion, evidence or in any legal or administrative procedure unless authorized by Eco Friendly Tiles Ltd.